
3Y0606C





Specifications

Family	SERIES 300 EAGLE
Application	Exit sign
Light source	6W LED
Functionality	battery pack , low/high
LoRa node	yes
Supply	230V AC/DC
Color Temperature (K)	4000K
Luminous flux (lm)	585lm (100%); 468 (80%); 351 (60%); 234lm (40%); 117lm (20%)
Luminous flux (lm) emergency	300lm (1h) - 100lm (3h)
Ambient temperature (C)	Average between -20 and +30
Color housing	Grey, RAL 7035
Color rendering index (Ra)	RA>80
Autonomy	1 hour 3 hours - adjustable
reading distance (m)	25
Impact resistance	IK08
Power factor	0,9
Optics	Fresnel
Autotest (ATS)	yes
Motion sensor	no
Assembly	Surface mount , Wall
Material housing	polycarbonate
Maintained / non maintained	adjustable
Ingress protection	IP42
Insulation class	Klasse II
Batterijverwarming	no
Light sensor	no
Details/particulars	LoRaWAN; lifetime >100.000 hrs (L80/B10)
Battery pack	NiMh 3,6V 2,2Ah Long Life High Temp
EAN	8718309388492

We reserve the right to alter specifications.

Datum download PDF: 29-10-2026

HBI Bisscheroux | Hofdwarsweg 14 | 6161 DD Geleen | T: +31 (0)46 - 475 65 72 | E: info@hbi-lighting.com