



Specifications

Family	SERIES 400 ECONOMY
Application	Emergency lighting
Light source	6W LED
Functionality	radar , battery pack , light sensor
LoRa node	no
Supply	230V AC/DC
Color Temperature (K)	4000K
Luminous flux (lm)	140 (low level) - 400 (high level)
Luminous flux (lm) emergency	220
Ambient temperature (C)	average between -5 and +25
Color housing	wit
Color rendering index (Ra)	>80
Autonomy	1 hour
Impact resistance	IK 08
Power factor	0.9
Optics	prismatic diffusor
Autotest (ATS)	yes
Motion sensor	yes
Assembly	Surface mount
Material housing	ABS + polycarbonate
Maintained / non maintained	ja
Ingress protection	IP 65
Power consumption	4,4W (low level) - 8,5W (high level)
Insulation class	Klasse I
Light sensor	yes
Details/particulars	designed for >100.000 hours
Battery pack	NiMh 3,6V 2,2Ah Long Life High Temp
EAN	8718309385644



We reserve the right to alter specifications.

Datum download PDF: 01-05-2026

HBI Bisscheroux | Hofdwarweg 14 | 6161 DD Geleen | T: +31 (0)46 - 475 65 72 | E: info@hbi-lighting.com