



Specifications

Family	SERIES 400 ECONOMY
Application	Emergency lighting
Light source	9W LED
Functionality	battery pack , low/high
LoRa node	no
Supply	230V AC/DC
Color Temperature (K)	4000K
Luminous flux (lm)	140 (L1) - 650 (L1+L2)
Luminous flux (lm) emergency	370
Ambient temperature (C)	average between -5 and +25
Color housing	wit
Color rendering index (Ra)	>80
Autonomy	1 hour
reading distance (m)	24
Impact resistance	IK 08
Power factor	0.9
Optics	hoogglans reflector, diepstralend
Autotest (ATS)	yes
Motion sensor	no
Assembly	Surface mount
Material housing	ABS + polycarbonate
Maintained / non maintained	adjustable
Ingress protection	IP 65
Power consumption	5,3W (L1) - 11,4W (L1+L2)
Insulation class	Klasse I
Light sensor	no
Details/particulars	Hoge lumenstroom in nood
Battery pack	NiMh 3,6V 2,2Ah Long Life High Temp
EAN	8718309386122



We reserve the right to alter specifications.

Datum download PDF: 15-06-2026

HBI Bisscheroux | Hofdarsweg 14 | 6161 DD Geleen | T: +31 (0)46 - 475 65 72 | E: info@hbi-lighting.com