



## Specifications

|                              |  |
|------------------------------|--|
| Family                       | SERIES 440 FORTEM  |
| Application                  | Emergency lighting   |
| Light source                 | 9W LED   |
| Functionality                | radar , light sensor , battery pack                              |
| LoRa node                    | yes  |
| Supply                       | 230V AC/DC   |
| Color Temperature (K)        | 4000K  |
| Luminous flux (lm)           | 720lm (100%), 580lm (80%), 440lm (60%), 290lm (40%), 150lm (20%) |
| Luminous flux (lm) emergency | 380lm - 1 hour   130lm - 3 hours (adjustable)                    |
| Ambient temperature (C)      | average between -20 and +25                                      |
| Color housing                | white, RAL 9003  |
| Color rendering index (Ra)   | >80  |
| Autonomy                     | 1 hour 3 hours - adjustable                                      |
| Impact resistance            | 3x IK10  |
| Power factor                 | 0.9  |
| Optics                       | Diffusor opal  |
| Autotest (ATS)               | yes  |
| Motion sensor                | yes  |
| Assembly                     | Surface mount , Ceiling , Wall                                   |
| Material housing             | polycarbonate  |
| Maintained / non maintained  | adjustable   |
| Ingress protection           | IP65   |
| Power consumption            | min. 1,8W - max. 8,7W  |
| Insulation class             | Klasse II  |
| Light sensor                 | yes  |
| Details/particulars          | LoRaWAN; lifetime >100.000 hrs (L80/B10)                         |
| Battery pack                 | NiMh 3,6V 2,2Ah Long Life High Temp                              |
| EAN                          | 8720246250220  |



We reserve the right to alter specifications.

Datum download PDF: 05-06-2026

HBI Bisscheroux | Hofdarsweg 14 | 6161 DD Geleen | T: +31 (0)46 - 475 65 72 | E: info@hbi-lighting.com