



Specifications

Family	SERIES 550 ALL-IN-ONE
Application	Emergency lighting
Light source	6W LED
Functionality	battery pack
LoRa node	no
Supply	230V AC/DC
Color Temperature (K)	4000K
Luminous flux (lm)	400lm (100%); 320lm (80%); 240lm (60%); 160lm (40%); 80lm (20%)
Luminous flux (lm) emergency	300lm (1h) - 100lm (3h)
Ambient temperature (C)	Average between -20 and +25
Color housing	black, RAL 7021
Color rendering index (Ra)	>80
Autonomy	adjustable 1h or 3h
Impact resistance	IK08
Power factor	0,9
Optics	diffusor & fresnel
Autotest (ATS)	yes
Motion sensor	no
Assembly	Surface mount
Material housing	polycarbonate
Maintained / non maintained	Emergency operation only
Ingress protection	IP40
Power consumption	2,4W
Insulation class	Klasse II
Light sensor	no
Details/particulars	Emergency luminaire including 3 phase rail adapter. Emergency operation only.
Battery pack	NiMh 3,6V 2,2Ah Long Life High Temp
EAN	8718309389055



We reserve the right to alter specifications.

Datum download PDF: 15-06-2026

HBI Bisscheroux | Hofdarsweg 14 | 6161 DD Geleen | T: +31 (0)46 - 475 65 72 | E: info@hbi-lighting.com