



## Specifications

|                              |   |
|------------------------------|---|
| Family                       | SERIES 550 ALL-IN-ONE   |
| Application                  | Exit sign   |
| Light source                 | 6W LED  |
| Functionality                | battery pack , low/high   |
| LoRa node                    | no  |
| Supply                       | 230V AC/DC  |
| Color Temperature (K)        | 4000K   |
| Luminous flux (lm)           | 400lm (100%); 320lm (80%); 240lm (60%); 160lm (40%); 80lm (20%)                     |
| Luminous flux (lm) emergency | black, RAL 7021   |
| Ambient temperature (C)      | +5 - +25  |
| Color housing                | zwart RAL 7021  |
| Color rendering index (Ra)   | >80   |
| Autonomy                     | adjustable 1h or 3h   |
| reading distance (m)         | 29 (Stylish Legend)   |
| Impact resistance            | IK 08   |
| Power factor                 | 0.9   |
| Optics                       | diffusor & fresnel  |
| Autotest (ATS)               | yes   |
| Motion sensor                | no  |
| Assembly                     | Surface mount , Ceiling , Wall  |
| Material housing             | polycarbonate   |
| Maintained / non maintained  | adjustable  |
| Ingress protection           | IP 40   |
| Power consumption            | 4,2W(20%) - 8,3W(100%)  |
| Insulation class             | Klasse II   |
| Light sensor                 | no  |
| Details/particulars          | lifetime >100.000 hrs (L80/B10); advice lumenoutput: low level 20% (dipswitch 1 ON) |
| Battery pack                 | NiMh 3,6V 2,2Ah Long Life High Temp   |
| EAN                          | 8718309386979   |



We reserve the right to alter specifications.

Datum download PDF: 05-06-2026

HBI Bisscheroux | Hofdarsweg 14 | 6161 DD Geleen | T: +31 (0)46 - 475 65 72 | E: info@hbi-lighting.com