



Specifications

Family	SERIES 550 ALL-IN-ONE
Application	Exit sign
Light source	6W LED
Functionality	battery pack , low/high
LoRa node	no
Supply	230V AC/DC
Color Temperature (K)	4000K
Luminous flux (lm)	400lm (100%); 320lm (80%); 240lm (60%); 160lm (40%); 80lm (20%)
Luminous flux (lm) emergency	black, RAL 7021
Ambient temperature (C)	+5 - +25
Color housing	zwart RAL 7021
Color rendering index (Ra)	>80
Autonomy	adjustable 1h or 3h
reading distance (m)	29 (Stylish Legend)
Impact resistance	IK 08
Power factor	0.9
Optics	diffusor & fresnel
Autotest (ATS)	yes
Motion sensor	no
Assembly	Surface mount , Ceiling , Wall
Material housing	polycarbonate
Maintained / non maintained	adjustable
Ingress protection	IP 40
Power consumption	4,2W(20%) - 8,3W(100%)
Insulation class	Klasse II
Light sensor	no
Details/particulars	lifetime >100.000 hrs (L80/B10); advice lumenoutput: low level 20% (dipswitch 1 ON)
Battery pack	NiMh 3,6V 2,2Ah Long Life High Temp
EAN	8718309386979



We reserve the right to alter specifications.

Datum download PDF: 07-03-2026

HBI Bisscheroux | Hofdarsweg 14 | 6161 DD Geleen | T: +31 (0)46 - 475 65 72 | E: info@hbi-lighting.com