



Specifications

| | |
|------------------------------|--|
| Family | SERIES 550 ALL-IN-ONE |
| Application | Exit sign |
| Light source | 6W LED |
| Functionality | battery pack , low/high |
| LoRa node | no |
| Supply | 230V AC/DC |
| Color Temperature (K) | 4000K |
| Luminous flux (lm) | 400lm (100%); 320lm (80%); 240lm (60%); 160lm (40%); 80lm (20%) |
| Luminous flux (lm) emergency | 300lm (1h) - 100lm (3h) |
| Ambient temperature (C) | average between 0 and +25 |
| Color housing | white, RAL 9003 |
| Color rendering index (Ra) | >80 |
| Autonomy | adjustable 1h or 3h |
| reading distance (m) | 29m (Stylish legend) 21m (Funtional legend) |
| Impact resistance | IK08 |
| Power factor | 0,9 |
| Optics | diffusor & fresnel |
| Autotest (ATS) | yes |
| Motion sensor | no |
| Assembly | Surface mount |
| Material housing | polycarbonate |
| Maintained / non maintained | yes |
| Ingress protection | klasse II |
| Power consumption | 4,2W |
| Insulation class | Klasse II |
| Light sensor | no |
| Details/particulars | Emergency luminaire including 3 phase rail adapter. Permanent and emergency operation. |
| Battery pack | NiMh 3,6V 2,2Ah Long Life High Temp |
| EAN | 8718309389048 |



We reserve the right to alter specifications.

Datum download PDF: 07-03-2026

HBI Bisscheroux | Hofdarsweg 14 | 6161 DD Geleen | T: +31 (0)46 - 475 65 72 | E: info@hbi-lighting.com