



Specifications

| | |
|------------------------------|---|
| Family | SERIES 550 ALL-IN-ONE |
| Application | Emergency lighting |
| Light source | 6W LED |
| Functionality | battery pack , low/high |
| LoRa node | yes |
| Supply | 230V AC/DC |
| Color Temperature (K) | 4000K |
| Luminous flux (lm) | 400lm (100%), 320lm (80%), 260lm (60%), 160lm (40%), 80lm (20%) |
| Luminous flux (lm) emergency | 380lm - 1 hour 240lm - 3 hours (adjustable) |
| Ambient temperature (C) | average between 0 and +25 |
| Color housing | Grey, RAL 7035 |
| Color rendering index (Ra) | >80 |
| Autonomy | 1 hour 3 hours - adjustable |
| Impact resistance | IK08 |
| Power factor | 0.8 |
| Optics | diffusor & fresnel lens |
| Autotest (ATS) | yes |
| Motion sensor | no |
| Assembly | Surface mount , Ceiling , Wall |
| Material housing | polycarbonate |
| Maintained / non maintained | adjustable |
| Ingress protection | IP40 |
| Power consumption | 1,5W (min) - 6,9W (max) |
| Insulation class | Klasse II |
| Light sensor | no |
| Details/particulars | LoRaWAN; lifetime >100.000 hrs (L80/B10) |
| Battery pack | NiMh 3,6V 2,2Ah Long Life High Temp |
| EAN | 8718309388669 |



We reserve the right to alter specifications.

Datum download PDF: 07-03-2026

HBI Bisscheroux | Hofdarsweg 14 | 6161 DD Geleen | T: +31 (0)46 - 475 65 72 | E: info@hbi-lighting.com