



Specifications

Family	SERIES 600 DISPLAY
Application	Exit sign
Light source	6W LED
Functionality	battery pack
LoRa node	no
Supply	230V AC/DC
Color Temperature (K)	4000K
Luminous flux (lm)	90lm (L1) - 300 (L1+L2)
Luminous flux (lm) emergency	160
Ambient temperature (C)	Average between -20 and +30
Color housing	grijs aluminium
Color rendering index (Ra)	>80
Weight (gr)	2280
Sizes of packaging (LxWxH)	380 x 84 x 190
Autonomy	1 uur
reading distance (m)	32
Power factor	0.9
Autotest (ATS)	yes
Assembly	Surface mount
Material housing	aluminium
Maintained / non maintained	ja
Ingress protection	IP 32
Power consumption	4,2W (L1) - 8,3W (L1+L2)
Insulation class	Klasse I
Details/particulars	lifetime >100.000 hrs (L80/B10)
Battery pack	NiMh 3,6V 2,2Ah Long Life High Temp
EAN	8718309385675



We reserve the right to alter specifications.

Datum download PDF: 15-06-2026

HBI Bisscheroux | Hofdarsweg 14 | 6161 DD Geleen | T: +31 (0)46 - 475 65 72 | E: info@hbi-lighting.com