



Specifications

| | |
|------------------------------|--------------------------------------|
| Family | SERIES 600 DISPLAY |
| Application | Exit sign |
| Light source | 12W LED |
| Functionality | battery pack |
| LoRa node | no |
| Supply | 230V AC/DC |
| Color Temperature (K) | 4000K |
| Luminous flux (lm) | 200lm (L1) - 600lm (L1+L2) |
| Luminous flux (lm) emergency | 180lm |
| Ambient temperature (C) | +5 - +25 |
| Color housing | grijs aluminium |
| Color rendering index (Ra) | >80 |
| Weight (gr) | 1200 |
| Sizes of packaging (LxWxH) | 525 x 280 x 84mm |
| Autonomy | 1 uur |
| reading distance (m) | 52 |
| Impact resistance | IK08 |
| Power factor | 0.9 |
| Optics | opaal diffusor |
| Dali | no |
| Autotest (ATS) | yes |
| Vf ≤ 200V | no |
| Vf ≤ 90V | no |
| Vf ≤ 55V | no |
| Motion sensor | no |
| Assembly | Surface mount |
| Material housing | aluminium |
| Maintained / non maintained | ja |
| Ingress protection | IP 32 |
| Power consumption | 5W (L1) - 11,6W (L1+L2) |
| Insulation class | Klasse I |
| Batterijverwarming | no |
| Light sensor | no |
| Details/particulars | lifetime >100.000hrs (L80/B10) |
| Battery pack | NiCd 3,6V / 1,6Ah High Temp (94143L) |
| EAN | 8718309386597 |



We reserve the right to alter specifications.

Datum download PDF: 21-04-2026

HBI Bisscheroux | Hofdarsweg 14 | 6161 DD Geleen | T: +31 (0)46 - 475 65 72 | E: info@hbi-lighting.com