



## Specifications

Family	SERIES 600 DISPLAY
Application	Exit sign
Light source	12W LED
Functionality	battery pack
LoRa node	no
Supply	230V AC/DC
Color Temperature (K)	4000K
Luminous flux (lm)	200lm (L1) - 600lm (L1+L2)
Luminous flux (lm) emergency	180lm
Ambient temperature (C)	+5 - +25
Color housing	grijs aluminium
Color rendering index (Ra)	>80
Weight (gr)	1200
Sizes of packaging (LxWxH)	525 x 280 x 84mm
Autonomy	1 uur
reading distance (m)	52
Impact resistance	IK08
Power factor	0.9
Optics	opaal diffusor
Dali	no
Autotest (ATS)	yes
Vf ≤ 200V	no
Vf ≤ 90V	no
Vf ≤ 55V	no
Motion sensor	no
Assembly	Surface mount
Material housing	aluminium
Maintained / non maintained	ja
Ingress protection	IP 32
Power consumption	5W (L1) - 11,6W (L1+L2)
Insulation class	Klasse I
Batterijverwarming	no
Light sensor	no
Details/particulars	lifetime > 100.000 hrs (L80/B10)
Battery pack	NiCd 3,6V / 1,6Ah High Temp (94143L)
EAN	8718309386603



We reserve the right to alter specifications.

Datum download PDF: 21-04-2026

HBI Bisscheroux | Hofdarsweg 14 | 6161 DD Geleen | T: +31 (0)46 - 475 65 72 | E: info@hbi-lighting.com