



Specifications

Family	SERIES 600 DISPLAY
Application	Exit sign
Light source	LED
Functionality	battery pack
LoRa node	yes
Supply	230V AC/DC
Color Temperature (K)	4000K
Luminous flux (lm)	200lm (L1) - 600lm (L1+L2)
Luminous flux (lm) emergency	180lm - 1 hour 60lm - 3 hour
Ambient temperature (C)	Average between -20 and +30
Color housing	grijs aluminium
Color rendering index (Ra)	>80
Sizes of packaging (LxWxH)	525 x 280 x 84mm
Autonomy	1 hour 3 hours - adjustable
reading distance (m)	52
Impact resistance	IK08
Power factor	0.9
Optics	opaal diffusor
Autotest (ATS)	yes
Assembly	Surface mount , Ceiling
Material housing	aluminium
Maintained / non maintained	ja
Ingress protection	IP32
Power consumption	5W (L1) - 11,6W (L1+L2)
Insulation class	Klasse I
Details/particulars	lifetime > 100.000hrs (L80/B10)
Battery pack	HBI NiMh 3.6V 2.2Ah stick Long Life High Temp P (art. 94223L)
EAN	8720246250442



We reserve the right to alter specifications.

Datum download PDF: 15-06-2026

HBI Bisscheroux | Hofdarsweg 14 | 6161 DD Geleen | T: +31 (0)46 - 475 65 72 | E: info@hbi-lighting.com