



Specifications

Family	SERIES 600 DISPLAY
Application	Exit sign
Light source	LED
Functionality	battery pack
LoRa node	yes
Supply	230V AC/DC
Color Temperature (K)	4000K
Luminous flux (lm)	600lm (100%) - 480lm (80%) - 360lm (60%) - 240lm (40%)
Luminous flux (lm) emergency	300lm
Ambient temperature (C)	-20 - +25
Color housing	grijs aluminium
Color rendering index (Ra)	>80
Sizes of packaging (LxWxH)	525 x 280 x 84mm
Autonomy	1 hour of 3 hour (adjustable)
reading distance (m)	52
Impact resistance	IK08
Power factor	0.9
Optics	opaal diffuser
Autotest (ATS)	yes
Assembly	Surface mount , Wall
Material housing	aluminium
Maintained / non maintained	ja
Ingress protection	IP32
Insulation class	Klasse I
Battery pack	HBI NiMh 3.6V 2.2Ah stick Long Life High Temp (art. 94223L)
EAN	8720246250459



We reserve the right to alter specifications.

Datum download PDF: 21-04-2026

HBI Bisscheroux | Hofdarsweg 14 | 6161 DD Geleen | T: +31 (0)46 - 475 65 72 | E: info@hbi-lighting.com