



## Specifications

Family	SERIES 700 LITE & SIGN
Application	Exit sign & emergency lighting
Light source	6W LED
Functionality	battery pack , low/high
LoRa node	no
Supply	230V AC/DC
Color Temperature (K)	4000K
Luminous flux (lm)	90 (L1) - 300 (L1+L2)
Luminous flux (lm) emergency	160
Ambient temperature (C)	+5 - +25
Color housing	wit RAL 9010
Color rendering index (Ra)	>80
Weight (gr)	2500
Sizes of packaging (LxWxH)	359 x 126 x 105
reading distance (m)	24
Power factor	0.9
Dali	no
Autotest (ATS)	yes
Motion sensor	no
Assembly	Recessed
Material housing	metaal
Maintained / non maintained	instelbaar
Ingress protection	IP 20
Power consumption	4,2W (L1) - 8,5W (L1+L2)
Insulation class	Klasse I
Batterijverwarming	no
Light sensor	no
Details/particulars	lifetime >100.000 hrs (L80/B10)
Battery pack	NiCd 3,6V / 1,6Ah High Temp (94143L)
EAN	8718309385729



We reserve the right to alter specifications.

Datum download PDF: 15-06-2026

HBI Bisscheroux | Hofdarsweg 14 | 6161 DD Geleen | T: +31 (0)46 - 475 65 72 | E: info@hbi-lighting.com