



## Specifications

Family	SERIES 900 LUNET
Application	Emergency lighting
Light source	26W LED
Functionality	battery pack , low/high
LoRa node	no
Supply	230V AC/DC
Color Temperature (K)	4000K
Luminous flux (lm)	664lm (low level) - 3320lm (high level)
Luminous flux (lm) emergency	410lm
Ambient temperature (C)	average between -5 and +25
Color housing	Grey, RAL 7035
Color rendering index (Ra)	>80
Autonomy	1 hour
Impact resistance	IK08
Power factor	0.92
Optics	opaal diffusor
Autotest (ATS)	yes
Motion sensor	no
Assembly	Surface mount
Material housing	polyester (housing); polycarbonaat (diffusor)
Maintained / non maintained	adjustable
Ingress protection	IP 66
Power consumption	7W (low level) - 27,5W (high level)
Insulation class	Klasse I
Light sensor	no
Details/particulars	lifetime >100.000 hrs (L80/B10)
Battery pack	NiMh 3,6V 2,2Ah Long Life High Temp
EAN	8718309387228



We reserve the right to alter specifications.

Datum download PDF: 05-06-2026

HBI Bisscheroux | Hofdwarweg 14 | 6161 DD Geleen | T: +31 (0)46 - 475 65 72 | E: info@hbi-lighting.com