



9L3000SRF1 (incl. through wiring 1 Phase)



Specifications

| | |
|----------------------------|--|
| Family | SERIES 900 LUNET |
| Application | General Lighting |
| Light source | 30W LED |
| Functionality | radar , light sensor |
| LoRa node | no |
| Supply | 230V AC/DC |
| Color Temperature (K) | 4000K |
| Luminous flux (lm) | 760 (low level) - 3580 (high level) |
| Ambient temperature (C) | average zwischen -5 und +25 |
| Color housing | Grey, RAL 7035 |
| Color rendering index (Ra) | >80 |
| Impact resistance | IK08 |
| Power factor | 0.92 |
| Optics | opaal diffusor |
| Autotest (ATS) | no |
| Motion sensor | yes |
| Assembly | Surface mount , Ceiling , Wall |
| Material housing | polyester (housing), polycarbonate (diffusor) |
| Ingress protection | IP66 |
| Power consumption | 7,5W (min) -28,3W (max) |
| Insulation class | Klasse I |
| Light sensor | yes |
| Details/particulars | Incl. through wiring 1 phase, lifetime >70.000 hrs (L80/B10) |
| EAN | 8718309387792 |



We reserve the right to alter specifications.

Datum download PDF: 05-06-2026

HBI Bisscheroux | Hofdarsweg 14 | 6161 DD Geleen | T: +31 (0)46 - 475 65 72 | E: info@hbi-lighting.com