



9L3030SRF1 (Incl. through wiring 1 Phase)



Specifications

Family	SERIES 900 LUNET
Application	Emergency lighting
Light source	30W LED
Functionality	radar , light sensor , battery pack
LoRa node	no
Supply	230V AC/DC
Color Temperature (K)	4000K
Luminous flux (lm)	760 (low level) - 3580 (high level)
Luminous flux (lm) emergency	400lm
Ambient temperature (C)	average zwischen -5 und +25
Color housing	Grey, RAL 7035
Color rendering index (Ra)	>80
Autonomy	1 Hour
Impact resistance	IK08
Power factor	0.9
Optics	opaal diffusor
Autotest (ATS)	yes
Motion sensor	yes
Assembly	Surface mount , Ceiling , Wall
Material housing	polyester (housing); policarbonate (diffusor)
Maintained / non maintained	adjustable
Ingress protection	IP66
Power consumption	7,5W (min) - 29,7W (max)
Insulation class	Klasse I
Batterijverwarming	no
Light sensor	yes
Details/particulars	Incl. through wiring 1 Phases; lifetime >70.000 hrs (L80/B10)
Battery pack	NiMh 3,6V 2,2Ah Long Life High Temp
EAN	8718309387815



We reserve the right to alter specifications.

Datum download PDF: 21-04-2026

HBI Bisscheroux | Hofdarsweg 14 | 6161 DD Geleen | T: +31 (0)46 - 475 65 72 | E: info@hbi-lighting.com