



## Specifications

|                              |   |
|------------------------------|---|
| Family                       | SERIES 900 LUNET  |
| Application                  | Emergency lighting  |
| Light source                 | LED   |
| Functionality                | light sensor , battery pack , low/high                          |
| LoRa node                    | yes   |
| Supply                       | 230V AC/DC  |
| Color Temperature (K)        | 4000K   |
| Luminous flux (lm)           | 664lm (low level) - 3320lm (high level)                         |
| Luminous flux (lm) emergency | 410   |
| Ambient temperature (C)      | -20 - +40   |
| Color housing                | grijs RAL 7035  |
| Color rendering index (Ra)   | >80   |
| Autonomy                     | adjustable: 1h of 3h  |
| Impact resistance            | IK08  |
| Power factor                 | 0.92  |
| Optics                       | opaal diffusor  |
| Autotest (ATS)               | yes   |
| Assembly                     | Surface mount , Ceiling , Wall                                  |
| Material housing             | polyester (housing); polycarbonaat (diffusor)                   |
| Maintained / non maintained  | adjustable  |
| Ingress protection           | IP66  |
| Power consumption            | 7W (low level) - 27,5W (high level)                             |
| Insulation class             | Klasse I  |
| Light sensor                 | yes   |
| Details/particulars          | LoRa, suitable for wireless remote management in Sqiippa Online |
| Battery pack                 | NiMh 3,6V 2,2Ah Long Life High Temp                             |
| EAN                          | 8720246251708   |



We reserve the right to alter specifications.

Datum download PDF: 23-04-2026

HBI Bisscheroux | Hofdwarweg 14 | 6161 DD Geleen | T: +31 (0)46 - 475 65 72 | E: info@hbi-lighting.com