



Specifications

| | |
|------------------------------|---|
| Family | SERIES 900 LUNET |
| Application | Emergency lighting |
| Light source | LED |
| Functionality | battery pack , low/high |
| LoRa node | yes |
| Supply | 230V AC/DC |
| Color Temperature (K) | 4000K |
| Luminous flux (lm) | 716lm (low level) - 3580lm (high level) |
| Luminous flux (lm) emergency | 400 |
| Ambient temperature (C) | -20 - +40 |
| Color housing | grijs RAL 7035 |
| Color rendering index (Ra) | >80 |
| Autonomy | adjustable 1h of 3h |
| Impact resistance | IK08 |
| Power factor | 0.92 |
| Optics | opaal diffusor |
| Autotest (ATS) | yes |
| Assembly | Surface mount , Ceiling , Wall |
| Material housing | polyester (housing); polycarbonaat (diffusor) |
| Maintained / non maintained | adjustable |
| Ingress protection | IP66 |
| Power consumption | 7W (low level) - 27,5W (high level) |
| Insulation class | Klasse I |
| Details/particulars | LoRa, suitable for wireless remote management in Sqippra Online |
| Battery pack | NiMh 3,6V 2,2Ah Long Life High Temp |
| EAN | 8718309388737 |



We reserve the right to alter specifications.

Datum download PDF: 05-06-2026

HBI Bisscheroux | Hofdwarweg 14 | 6161 DD Geleen | T: +31 (0)46 - 475 65 72 | E: info@hbi-lighting.com