



Specifications

Family	SERIES 900 LUNET
Application	Emergency lighting
Light source	LED
Functionality	radar , light sensor , battery pack
LoRa node	yes
Supply	230V AC/DC
Color Temperature (K)	4000K
Luminous flux (lm)	716lm (low level) - 3580lm (high level)
Luminous flux (lm) emergency	400
Ambient temperature (C)	-20 - +40
Color housing	grijs RAL 7035
Color rendering index (Ra)	>80
Autonomy	adjustable 1h of 3h
Impact resistance	IK08
Power factor	0.92
Optics	opaal diffusor
Autotest (ATS)	yes
Motion sensor	yes
Assembly	Surface mount , Ceiling , Wall
Material housing	polyester (housing); polycarbonaat (diffusor)
Maintained / non maintained	adjustable
Power consumption	7W (low level) - 27,5W (high level)
Insulation class	Klasse I
Light sensor	yes
Details/particulars	LoRa, suitable for wireless remote management in Sqiippa Online
Battery pack	NiMh 3,6V 2,2Ah Long Life High Temp
EAN	8718309388744



We reserve the right to alter specifications.

Datum download PDF: 07-03-2026

HBI Bisscheroux | Hofdwarweg 14 | 6161 DD Geleen | T: +31 (0)46 - 475 65 72 | E: info@hbi-lighting.com