



Specifications

| | |
|----------------------------|--|
| Family | SERIES 110 CIRCUM |
| Application | General Lighting |
| Light source | 12W LED |
| Functionality | radar , light sensor |
| LoRa node | no |
| Supply | 230V AC/DC |
| Color Temperature (K) | 3000K |
| Luminous flux (lm) | 1350lm (100%), 1080lm (80%), 810lm (60%), 540lm (40%), 270lm (20%) |
| Ambient temperature (C) | average between -20 and +25 |
| Color housing | white, RAL9003 |
| Color rendering index (Ra) | >80 |
| Weight (gr) | 1490 |
| Sizes of packaging (LxWxH) | 350 x 370 x 105 mm |
| Impact resistance | 3 x IK10 (65 joules) |
| Power factor | 0,9 |
| Motion sensor | yes |
| Assembly | Surface mount , Ceiling , Wall |
| Material housing | polycarbonate |
| Ingress protection | IP65 |
| Power consumption | 16W (100%), 12,5W (80%), 9,5W (60%), 6,5W (40%), 3,6W (20%) |
| Insulation class | Klasse II |
| Light sensor | yes |
| Details/particulars | lifetime >100.000 hours (L80/B10) |
| EAN | 8718309389192 |



We reserve the right to alter specifications.

Datum download PDF: 01-05-2026

HBI Bisscheroux | Hofdarsweg 14 | 6161 DD Geleen | T: +31 (0)46 - 475 65 72 | E: info@hbi-lighting.com