



Specifications

| | |
|----------------------------|---------------------------------|
| Family | SERIES 200 POLAREM |
| Application | General Lighting |
| Light source | 5W LED |
| Functionality | light sensor , low/high |
| LoRa node | no |
| Supply | 230V AC/DC |
| Color Temperature (K) | 4000K |
| Luminous flux (lm) | 80lm(L1) - 425lm (L1 + L2) |
| Ambient temperature (C) | average between -25 and +40 |
| Color housing | Grey, RAL 7035 |
| Color rendering index (Ra) | >80 |
| Sizes of packaging (LxWxH) | 265 x 148 x 99 |
| Impact resistance | IK10 |
| Power factor | 0.9 |
| Optics | lens corridor |
| Motion sensor | no |
| Assembly | Surface mount , Ceiling |
| Material housing | polycarbonate |
| Ingress protection | IP 65 |
| Power consumption | 7W (100%) > 1,3W (20%) |
| Insulation class | Klasse II |
| Light sensor | yes |
| Details/particulars | lifetime >100.000 hrs (L80/B10) |
| EAN | 8718309385316 |



We reserve the right to alter specifications.

Datum download PDF: 04-06-2026

HBI Bisscheroux | Hofdwarweg 14 | 6161 DD Geleen | T: +31 (0)46 - 475 65 72 | E: info@hbi-lighting.com