




2L0505WSE (wall, diffuse, emergency)



Specifications

Family	SERIES 200 POLAREM
Application	Exit sign & emergency lighting
Light source	5W LED
Functionality	light sensor , battery pack , low/high
LoRa node	no
Supply	230V AC/DC
Color Temperature (K)	4000K
Luminous flux (lm)	570lm (100%); 456lm (80%); 342lm (60%); 228lm (40%); 114lm (20%)
Luminous flux (lm) emergency	365lm (1h) - 122lm (3h)
Ambient temperature (C)	average between -25 and +40
Color housing	Grey, RAL 7035
Color rendering index (Ra)	>80
Autonomy	adjustable 1h or 3h
Impact resistance	IK10
Power factor	0.9
Optics	Square Lens diffuse
Autotest (ATS)	yes
Motion sensor	no
Assembly	Surface mount , Wall
Material housing	polycarbonate
Maintained / non maintained	ja
Ingress protection	IP 65
Power consumption	3,6W(20%) / 8,4W (100%)
Insulation class	Klasse II
Light sensor	yes
Details/particulars	lifetime >100.000 hrs (L80/B10)
Battery pack	NiMh 3,6V 2,2Ah Long Life High Temp
EAN	8718309385453



We reserve the right to alter specifications.

Datum download PDF: 05-06-2026

HBI Bisscheroux | Hofdarsweg 14 | 6161 DD Geleen | T: +31 (0)46 - 475 65 72 | E: info@hbi-lighting.com